

INDOFIL CPE 1350

INTRODUCTION:

INDOFIL CPE 1350 is general purpose impact improver with high molecular weight, good mechanical performance and impact improver for rigid plastic products.

SPECIFICATION:

Property	Specification
Chlorine Content (%)	35 ± 1
Volatile Matter (%)	≤ 0.5
Thermal Decomposition (°C)	≥ 170
Bulk Density (g/cm ³)	≥ 0.5
Elongation at Break (%)	≥ 700
Impurity Particles (PC/50 g)	< 25
Rate of Filtration (40 Mesh)	≥ 98

APPLICATION:

- PVC door and window profiles, siding, sheet, fence, pipes and conduits.

DOSAGE:

- Dosage varies with applications.

PACKAGING AND STORAGE:

- INDOFIL CPE 1350 is available in 25 kg bags with shelf life of 12 months when stored in sealed condition in a cool and dry place.

DISCLAIMER: The information, illustrations and suggestions of the Company herein are based on the results of tests and experiments conducted on the products. Nothing herein should be construed as a warranty or guarantee of whatsoever nature for which the Company assumes any legal responsibility, as conditions and methods of use of the products are beyond the control of the Company. It is left to the absolute discretion and knowledge of the prospective user to determine the suitability of the products and suggestions before procuring and adopting them on commercial scale. Nothing herein is to be construed as permission, inducement or recommendation to practice any patented invention without a proper license."