

## **INDOFIL PMA-175F (Lubricating Processing Aid for PVC)**

### **INTRODUCTION:**

INDOFIL PMA-175F is an acrylic polymer having strong external lubricating and processing aid properties for rigid PVC. This is generally used in conjunction with main processing aid.

Advantages of INDOFIL PMA-175F has advantages like reduced sticking to hot melt surfaces at high temperatures, Improved clarity and gloss, elimination of plate out, controlled fusion, eliminates surface defects. It is suitable for opaque application

### **SPECIFICATION:**

<b>Property</b>	<b>Specification</b>
Appearance	White free flowing powder
Bulk Density	0.38 to 0.45
Moisture Content	Max. 1.0%
Sieve Test Retention	
60 Mesh	Max. 10
100 Mesh	Max 20
200 Mesh	Max 60

### **APPLICATION:**

- For PVC Casing pipes, Column Pipes and other kind of pipes
- Window and Door Profiles
- PVC Foam Sheet, Foam Core pipes

### **DOSAGE:**

- Recommended dosage 1.0-3.0 Phr.

### **PACKAGING:**

- INDOFIL PMA-175F is available in 25 kgs bags.

DISCLAIMER: The information, illustrations and suggestions of the Company herein are based on the results of tests and experiments conducted on the products. Nothing herein should be construed as a warranty or guarantee of whatsoever nature for which the Company assumes any legal responsibility, as conditions and methods of use of the products are beyond the control of the Company. It is left to the absolute discretion and knowledge of the prospective user to determine the suitability of the products and suggestions before procuring and adopting them on commercial scale. Nothing herein is to be construed as permission, inducement or recommendation to practice any patented invention without a proper license."