



**INDOFIL INDUSTRIES LIMITED**  
Kalpataru Square, 4<sup>th</sup> Floor  
Kondivita Road, Off Andheri Kurla Road  
Andheri(E), Mumbai- 400 059, India  
**Tel : 022-6663 7373 Fax – 022-2832 2276**  
**E-mail : mktindl-icc@modi.com**



---

## TECHNICAL DATA SHEET

---

### INDOFIL FRA 3

**INDOFIL FRA 3** is a specially designed water based flame retardant formulation. The product has a soft handle. The product is recommended for various coating especially back coating of automotive application.

#### TYPICAL PROPERTIES :

- Appearance : white thick paste
- pH (as is) : 7-9
- Solid content : 40+/-2
- Viscosity @ 25°C (Model) : 10000-15000 cps (6/20, Brookfield RV)

#### CHARACTERISTICS:

- ✓ Conforms FM VSS 302 test
- ✓ Soft handle
- ✓ Excellent strength of coated film
- ✓ Can be applied to various applications
- ✓ Very Good abrasion resistance
- ✓ Good flexibility

The information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. is to the best of our Knowledge, Experience, However without any warranty.

## **APPLICATION :**

**INDOFIL FRA 3** can be applied for automotive back coating applications which gives excellent flame retardant performance along with required coating effect. The applied fabric passes FM VSS 302 test required for such application. INDOFIL FRA 3 can also be applied to other coating applications where flame retardant properties are required . It can also be formulated or diluted to various degree as per end requirements.

## **STORAGE**

Please store in cool dry place away from sunlight .When stored under standard storage conditions product will remain stable for 12 months.

## **SHELF LIFE**

If stored in the recommended condition, product has a shelf life of one year from the date of manufacturing .

## **PACKING INFORMATION**

INDOFIL FRA 3 is available in 200 kg open top PE drum.

The information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. is to the best of our Knowledge, Experience, However without any warranty.