



INDOFIL CHEMICALS COMPANY
Kalpataru Square, 4th Floor
Kondivita Road, Off Andheri Kurla Road
Andheri(E), Mumbai- 400 059, India
Tel : 022-9993 7373 Fax – 022-2832 2276
E-mail : mktindl-icc@modi.com



TECHNICAL DATA SHEET

INDOFIL SKP

White lacquer, high brilliancy and elasticity,
for knitted and elastic fabrics.

CHARACTERSTICS :

Chemical Nature	:	TiO ₂ dispersion(Rutile)& special Binders
Appearance	:	Thick Paste
Color	:	White
pH as such	:	8 +/- 1
Viscosity @25 Deg.C	:	35000 – 75000 cps

PROPERTIES :

- A similar effect “ Pastisol” is achieved in aqueous systems.
- Excellent brightness and very good elasticity printings.
- Excellent washing a rubbing fastness.
- Soft handle.
- Very good covering power on dark ground as it is or colored.
- This is compatible with printing pastes.



APPLICATION :-

- INDOFIL SKP is applied as it is when a white and bright covering is needed.
- Colored effect can be achieved by addition of 40 – 100 gm/Kg of pigment depend on medium – dark shades.

FIXING :-

To enhance fixation properties, addition of 1 – 2 % of INDOFIL FIXER LF and 1 – 2 % of Catalyst (25%) in INDOFIL SKP is recommended.

- Treat the printing with dry heat :

3 – 4 minutes at 140 – 150 Deg. C

This treatment is necessary to get the maximum fastness.

The suggestion and data in this bulletin based on information we believe to be reliable. It is offered in good faith, but WITHOUT GUARANTEE, as the conditions and methods of the use of our products are beyond our control. We ALWAYS recommend that the prospective user should determine the suitability of our products and suggestions on an experimental basis first, Before ADAPTING on a commercial scale.

